

GLASS PASSIVATED BRIDGE RECTIFIERS

**REVERSE VOLTAGE – 400 to 1000 Volts
FORWARD CURRENT – 4.0 Ampere**


FEATURES

- Rating to 1000V PRV
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- The plastic material has UL flammability classification 94V-0
-

MECHANICAL DATA

- Polarity : As marked on body
- Weight : 0.05 ounces, 1.52 grams
- Mounting position : Any

KBP



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

| CHARACTERISTICS | SYMBOL | KBP404G | KBP406G | KBP408G | KBP410G | UNIT |
|--|---|----------------|---------|---------|---------|----------------------|
| Device indicate code | Code | KBP404G | KBP406G | KBP408G | KBP410G | --- |
| Maximum Repetitive Peak Reverse Voltage | V_{RRM} | 400 | 600 | 800 | 1000 | V |
| Maximum RMS Voltage | V_{RMS} | 280 | 420 | 560 | 700 | V |
| Maximum DC Blocking Voltage | V_{DC} | 400 | 600 | 800 | 1000 | V |
| Maximum Average Forward Rectified Current @ $T_C=105^\circ\text{C}$ | $I_{(AV)}$ | 4.0 2.0 | | | | A |
| Peak Forward Surge Current @ $T_j = 25^\circ\text{C}$ 8.3ms single half sine-wave @ $T_j = 125^\circ\text{C}$ | I_{FSM} | 130 110 | | | | A |
| Peak Forward Surge Current @ $T_j = 25^\circ\text{C}$ 1.0ms single half sine-wave @ $T_j = 125^\circ\text{C}$ | I_{FSM} | 260 220 | | | | A |
| Maximum Forward Voltage at 4.0A DC | V_F | 1.1 | | | | V |
| Maximum DC Reverse Current at rated Blocking Voltage @ $T_j=25^\circ\text{C}$ @ $T_j=125^\circ\text{C}$ | I_R | 5.0 500 | | | | μA |
| I^2t Rating for fusing ($3\text{ms} \leq t \leq 8.3\text{ms}$) | I^2t | 50 | | | | A^2S |
| Typical Junction Capacitance per element (Note 1) | C_J | 40 | | | | pF |
| Typical thermal resistance (Unit mounted on 75mmx75mmx1.6mm Copper plate heatsink.) | $R_{\theta JC}$ $R_{\theta JL}$ $R_{\theta JA}$ | 6 8 15 | | | | $^\circ\text{C/W}$ |
| Typical thermal resistance (without heatsink) | $R_{\theta JC}$ $R_{\theta JL}$ $R_{\theta JA}$ | 14 20 40 | | | | $^\circ\text{C/W}$ |
| Operation and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | | | | $^\circ\text{C}$ |

Note : (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL JUNCTION CAPACITANCE




FIG.4- TYPICAL FORWARD CHARACTERISTICS




FIG.5- TYPICAL REVERSE CHARACTERISTICS




FIG.6- NON-REPETITIVE SURGE CURRENT

