

FEATURES


- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- Dual rectifier construction
- High temperature soldering guaranteed:260° C/10 seconds,, 0.25"(6.35mm)from case
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

MECHANICAL DATA

- Case: JEDEC ITO-220AB molded plastic body
- Terminals: Lead solderable per MIL-STD-750,method 2026
- Polarity: As marked
- Mounting Position: Any
- Weight: 0.08ounce, 2.24 gram



ITO-220AB



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load, derate by 20%.)

	Symbols	MBRF 1620CT	MBRF 1630CT	MBRF 1640CT	MBRF 1650CT	MBRF 1660CT	MBRF 1680CT	MBRF 16100CT	MBRF 16150CT	MBRF 16200CT	Units						
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	150	200	Volts						
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	105	140	Volts						
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	150	200	Volts						
Maximum average forward rectified current (see Fig.1)	I(AV)	8.0 16.0									Amps						
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	200.0									Amps						
Maximum instantaneous forward voltage at 16.0 A	V _F	0.60		0.75		0.85		0.90		0.95							
Maximum instantaneous reverse current at rated DC blocking voltage (Note 1)	I _R	0.2		30		50											
Typical thermal resistance (Note 2)	R _{JC}	3.0									C/W						
Operating junction temperature range	T _J	-65 to +150									C						
Storage temperature range	T _{STG}	-65 to +150									C						

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle

2.Thermal resistance from junction to case

[Http://www.gmsemi.com](http://www.gmsemi.com)

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL JUNCTION CAPACITANCE




FIG.5-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL REVERSE CHARACTERISTICS

